



DN	NPS	Zyl.Ø	ØA	ØB	C	D	E	F	G	ØH	ØK	ØL	ØM	T	kg
50	2"	40	50	165	91	43	415	252	110	G1/4"	125	-	4xM16	15	14
65	2 1/2"	40	50	185	91	46	435	257	115	G1/4"	145	-	4xM16	18	16
80	3"	40	50	200	91	46	501	278	139	G1/4"	160	4xØ18	4xM16	14	19
100	4"	40	50	220	96	52	563	349	152	G1/4"	180	4xØ18	4xM16	16	23
125	5"	63	75	250	96	56	647	357	160	G1/4"	210	4xØ18	4xM16	18	31
150	6"	63	75	285	104	56	750	467	179	G1/4"	240	4xØ22	4xM20	17	42
200	8"	63	75	340	104	60	830	497	209	G1/4"	295	4xØ22	4xM20	18	51
250	10"	63	75	395	141	68	1033	660	257	G1/4"	350	6xØ22	6xM20	21	77
300	12"	80	95	445	141	78	1127	700	297	G1/4"	400	6xØ22	6xM20	22	106

Steuerdruck für Hydraulik-Zylinder / operating pressure for hydraulic cylinder: 120 bar

Max. Betriebsdruck / max. working pressure: 10 bar

Änderungen vorbehalten  
subject to changes